




## FEATURES:-

- ✓ Supports 2x barriers ie. up to 1x in & 1x Out (expandable to 2x in & 2x out barriers)
- ✓ Supports up to 150k users & 80k events
- ✓ Supports firmware upgrade via IE
- ✓ Native IP with Peer to Peer communication
- ✓ High speed data polling to Server
- ✓ Compatible with various reader technologies
- ✓ Interlocking
- ✓ Built-in web server
- ✓ AES- 128 Encryption



## SMART ARCHITECTURE

### Effective Infrastructure

Leverage on the usage of existing network infrastructure, hence saving your cost.

### Adaptive Network Bandwidth

High bandwidth with high speed polling transmits data easily, enabling real-time transaction to the users.

## ACTIVE ENVIRONMENT

### Client to Server Environment

Communication between Server and FALCO controllers happens whenever an event is active on the controller.

### Peer to Peer Communication

Communication between one controller with another controller without the need of the database server acting as the facilitator.

## ADVANCED TECHNOLOGY

### High Speed Transmission

-Patented card searching algorithm to search card database within 1 second for controller memory of 150k users.

### Secure Technology

-FALCO proprietary protocol utilized.

-Integrated power supply module ensures stable operation despite electricity cut-off

-Door controller and the relay are placed in secure location for the better security

### Larger Storage

-Unbeatable technology enables Falco controller to support up to 150k users & 80k events memory.




# IP CAR PARK CF CONTROLLER

## SPECIFICATION:-


PROCESSING UNIT	Freescale CF microcontroller 32 bits @ 60MHz
MEMORY	1024 kb EEPROM & 16 Mb FLASH
BATTERY CHARGER	12 VDC / 7AH (Onboard battery backup charger)
POWER	14.5 VAC @ 12 VDC (Onboard power supply module max 2.0A)
READER SUPPORTED	1 door (2 readers) 1 x In, 1 x Out
READER TECHNOLOGY	Standard Wiegand format (26 bit -64 bit)
USERS / HISTORY	Standard 70k users, 40k events, upgradable to 150k
COMMUNICATION	RJ45 Ethernet/ 10/100 Base-T ( Max 100m / 328ft.)
NETWORK	TCP/IP, ARP, DHCP
INPUTS FUNCTIONALITY	Fire input/ exit push button / door contact/ tamper
CONTROLLER	Support 2 destinations IP address
DIMENSION / WEIGHT	PCB board = 137 (L) x117 (W) x 15.5 (H) mm / 25g
SECURITY ENCRYPTION	AES-128 bit (BI-DIRECTIONAL)
OPERATING TEMPERATURE	0°C ~ 55°C / 32° ~ 165°F (subject to battery specifications)
HUMIDITY	0 ~ 85% Humidity (relative non-condensing)
USER CARD EXPIRATION	YES
CERTIFICATIONS	CE RoHS

## ORDER INFORMATION :-




**Car Park Controller**  
Model : CTRL-1DRCAR-CF16M/IP(2.0A)-PCB

## FALCO CAR PARK TCP/IP SITE SYSTEM ARCHITECTURE



## FALCO CAR PARK VIDEO COMPARISON ARCHITECTURE



## ACCESSORIES :-



**Metal Casing**  
Model : EMPTY CONTROL PANEL BOX



**Transformer**  
Model : SF-0523-PT TRANSFORMER  
15.0V@3.0A



**12V DC BATTERY**  
Model : FA12-7E BATTERY